

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: 494745
Product Name: ZenWax Polish
Revision Date: Jul 22, 2020
Version: 2.0
Manufacturer's Name: Zenex International
Address: 1 Zenex Circle Cleveland, OH, US, 44146
Emergency Phone: 1-800-535-5053
Information Phone Number: (440)-232-4155
Fax:
Product/Recommended Uses: Wax and Shine

Date Printed: Jul 22, 2020
Supersedes Date: Aug 10, 2018

SECTION 2) HAZARDS IDENTIFICATION

Classification

Aerosols - Category 1
Gases Under Pressure - Liquefied Gas
Aspiration Hazard - Category 1
Skin Sensitizer - Category 1

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H222 - Extremely flammable aerosol.
H280 - Contains gas under pressure; may explode if heated.

Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways.
H317 - May cause an allergic skin reaction.

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements - Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing mist, vapors or spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, eye protection and face protection.

Precautionary Statements - Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or a rash occurs: Get medical attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P405 - Store locked up.

P403 - Store in a well-ventilated place.

Precautionary Statements - Disposal

P501 - Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0068476-86-8	Petroleum gases, liquefied, sweetened	5% - 12%
0064742-47-8	ISOPARAFFINIC PETROLEUM DISTILLATE	5% - 11%
0092704-41-1	Kaolin, calcined	2% - 4%
0068155-20-4	Amides, tall-oil fatty, N,N-bis(hydroxyethyl)	1.2% - 3%
0063148-62-9	Silicone	0.1% - 2%
0068647-72-3	Terpenes and Terpenoids, sweet orange-oil	0.1% - 0.8%
0000110-91-8	MORPHOLINE	0.1% - 0.6%
0000080-54-6	Benzenepropanal, 4-(1,1-dimethylethyl)-.alpha.-methyl-	0.1% - 0.2%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If exposed/feel unwell/concerned: Get medical attention.

Eliminate all ignition sources if safe to do so.

Eye Contact

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

Ingestion

Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

Most Important Symptoms/Effects, Acute and Delayed

No data available.

Indication of Immediate Medical Attention and Special Treatment Needed

No data available.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only. Do not direct a solid stream of water or foam into hot, burning pools. This may result in frothing and increased fire intensity.

Unsuitable Extinguishing Media

No data available.

Specific Hazards in Case of Fire

Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Product is highly flammable and forms explosive mixtures with air, oxygen, and all oxidizing agents. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a build up of internal pressures. Cool with water.

Empty Containers retain product residue which may exhibit hazards of material; therefore do not pressurize, cut, glaze, weld or use for any other purposes.

Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors.

Fire-Fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment

Wear liquid tight chemical protective clothing in combination with positive pressure self-contained breathing apparatus (SCBA).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Absorb liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

SECTION 7) HANDLING AND STORAGE

General

Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally.

Ventilation Requirements

Use in a well-ventilated place.

Storage Room Requirements

Store and use in a cool, dry, well-ventilated area. Do not store above 120°F. See product label for additional information.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Wear safety glasses with side shields. Eyewash stations and showers should be available in areas where this material is used and stored.

Skin Protection

Use solvent-resistant protective gloves for prolonged or repeated contact.

Respiratory Protection

Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Appropriate Engineering Controls

Ventilation should be sufficient to prevent inhalation of any vapors.

Chemical Name	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)
2-METHOXYETHANOL	80	25			1	1		0.1
DIETHANOLAMINE							1 (IFV)	
ISOPARAFFINIC PETROLEUM DISTILLATE	2000	500				1	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];	(L)[N159](L)[N800]
MORPHOLINE	70	20			1	1		20
Petroleum gases, liquefied, sweetened	2000	500				1		
TITANIUM DIOXIDE	15					1	10	

Chemical Name	NIOSH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
2-METHOXYETHANOL					Hematologic eff; repro eff	Skin; BEI	0.3	0.1
DIETHANOLAMINE				A3	Liver & kidney	Skin; A3	15	3

MINE					dam			
ISOPARAFFINI C PETROLEUM DISTILLATE				[A2[N159]A2 [N800]]; [A4 [N159]A4 [N800]];	URT irr [N159]URT irr [N800]	[A2[N159]A2 [N800]]; [A4 [N159]A4 [N800]];		
MORPHOLINE	30			A4	Eye dam; URT irr	Skin; A4	70	20
Petroleum gases, liquefied, sweetened								
TITANIUM DIOXIDE				A4	LRT irr	A4		b

Chemical Name	NIOSH STEL (mg/m3)	OSHA STEL (ppm)	NIOSH Carcinogen
2-METHOXYETHANOL			
DIETHANOLAMINE			
ISOPARAFFINI C PETROLEUM DISTILLATE			
MORPHOLINE	105		
Petroleum gases, liquefied, sweetened			
TITANIUM DIOXIDE			1

(C) - Ceiling limit, (IFV) - Inhalable fraction and vapor, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, dam - Damage, eff - Effects, irr - Irritation, LRT - Lower respiratory tract, repro - reproductive, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	7.69 lb/gal
Density VOC	0.78 lb/gal
% VOC	10.14%
<hr/>	
Appearance	N.A.
Odor Threshold	N.A.
Odor Description	N.A.
pH	N.A.
Water Solubility	N.A.
Flammability	Flash point below 73°F/23°C
Vapor Pressure	N.A.
Flash Point	N.A.
Viscosity	N.A.
Lower Explosion Level	N.A.
Upper Explosion Level	N.A.
Vapor Density	N.A.
Melting Point	N.A.

Freezing Point	N.A.
Low Boiling Point	N.A.
High Boiling Point	N.A.
Decomposition Pt	N.A.
Auto Ignition Temp	N.A.
Evaporation Rate	Slower than ether

SECTION 10) STABILITY AND REACTIVITY

Stability

Stable under normal storage and handling conditions.

Conditions to Avoid

Avoid heat, sparks, flame, high temperatures and contact with incompatible materials.

Dropping containers may cause bursting.

Incompatible Materials

Avoid strong oxidizers, reducers, acids, and alkalis.

Hazardous Reactions/Polymerization

Will not occur.

Hazardous Decomposition Products

No data available.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

No data available.

Likely Route of Exposure

Inhalation, ingestion, skin absorption.

Serious Eye Damage/Irritation

No data available.

Carcinogenicity

No data available.

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Respiratory/Skin Sensitization

May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure

No data available.

Specific Target Organ Toxicity - Repeated Exposure

No data available.

Aspiration Hazard

May be fatal if swallowed and enters airways.

Acute Toxicity

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

If swallowed, can easily enter the airways and could result in aspiration pneumonitis. Inhalation of high concentrations may cause dizziness, anesthesia, unconsciousness.

Potential Health Effects - Miscellaneous

0000109-86-4 2-METHOXYETHANOL

The substance may have effects on the blood and bone marrow. This may result in anaemia and lesions of blood cells.

0013463-67-7 TITANIUM DIOXIDE

Is an IARC, NTP or OSHA carcinogen. In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m³ respirable titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was overwhelmed and that the results at the massive 250 mg/m³ level are not relevant to the workplace. Results of a DuPont epidemiology study showed that employees who had been exposed to Titanium Dioxide were at no greater risk of developing lung cancer than were employees who had not been exposed to Titanium dioxide. No pulmonary fibrosis was found in any of the employees and no association was observed between Titanium dioxide exposure and chronic respiratory disease or x-ray abnormalities. Based on the results of this study DuPont concludes that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.'

0000110-91-8 MORPHOLINE

LC50 (rat): 2250 ppm/duration not reported (male rat) (1,9); 2150 ppm/duration not reported (female rat) (1,9); greater than 22.2 mg/L (6240 ppm)/1-hr exposure (12)

LC50 (mouse): 1320 mg/m³ (371 ppm)/2-hr exposure (reported but cannot be confirmed)

LD50 (oral, rat): 1600 mg/kg (7,12,13); 1050 mg/kg (3,7,9,12)

LD50 (oral, mouse): 525 mg/kg (16); 720 mg/kg (15)

LD50 (oral, guinea pig): 900 mg/kg (7,12,13)

LD50 (skin, rabbit): 0.5 mL/kg/24-hr (500 mg/kg/24-hr) (undiluted) (3,7,12,16)

Lethal dose (oral, rat or guinea pig): 0.1 g/kg (undiluted, not neutralized); all animals died rapidly. When diluted with 4 volumes of water, the minimum lethal dose was 0.9 g/kg (guinea pig) or 1.6 g/kg (rat) (13).

0000111-42-2 DIETHANOLAMINE

LD50 (oral, rat): Values have been reported ranging from 710-3540 mg/kg(1,2,3,4,5)

LD50 (oral, mouse): 3300 mg/kg (1)

LD50 (oral, guinea pig): 2000 mg/kg (1)

LD50 (dermal, rabbit): 12200 mg/kg (unverifiable; this value seems inappropriately high; see skin absorption below) (1)

0000109-86-4 2-METHOXYETHANOL

LC50 (mouse): 1480 ppm (7-hour exposure) (1)

LD50 (oral, rat): 2460 mg/kg (19); 3250 mg/kg (18)

LD50 (oral, guinea pig): 950 mg/kg (18,19)

LD50 (oral, rabbit): 890 mg/kg (18)

LD50 (dermal, rabbit): 1300 mg/kg (cited as 1.34 mL/kg) (24-hours contact)(18)

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

No data available.

Persistence and Degradability

No data available.

Bio-Accumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

	U.S. DOT Information	IMDG Information	IATA Information
UN number:	UN1950	UN1950	UN1950
Proper shipping name:	Aerosols	Aerosols	Aerosols, flammable
Hazard class:	2.1	2.1	2.1
Packaging group:	NA	NA	NA
Hazardous substance (RQ):	No Data Available		
Marine Pollutant:	No Data Available	No Data Available	
Note / Special Provision:	(LTD QTY)	(LTD QTY)	(LTD QTY)
Toxic-Inhalation Hazard:	No Data Available		

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0068476-86-8	Petroleum gases, liquefied, sweetened	5% - 12%	SARA312, TSCA, OSHA
0064742-47-8	ISOPARAFFINIC PETROLEUM DISTILLATE	5% - 11%	SARA312, VOC, TSCA, ACGIH, OSHA
0092704-41-1	Kaolin, calcined	2% - 4%	SARA312, TSCA
0068155-20-4	Amides, tall-oil fatty, N,N-bis (hydroxyethyl)	1.2% - 3%	SARA312, TSCA
0063148-62-9	Silicone	0.1% - 2%	SARA312, TSCA
0068647-72-3	Terpenes and Terpenoids, sweet orange-oil	0.1% - 0.8%	SARA312, TSCA
0000110-91-8	MORPHOLINE	0.1% - 0.6%	SARA312, VOC, TSCA, ACGIH, OSHA
0000080-54-6	Benzenepropanal, 4-(1,1-dimethylethyl)-.alpha.-methyl-	0.1% - 0.2%	SARA312, TSCA
0013463-67-7	TITANIUM DIOXIDE	Trace	SARA312, TSCA, ACGIH, California Proposition 65 Cancer, OSHA
0000111-42-2	DIETHANOLAMINE	Trace	SARA313, CERCLA, HAPS, SARA312, VOC, TSCA, ACGIH, California Proposition 65 Cancer
0000078-70-6	1,6-Octadien-3-ol, 3,7-dimethyl-	Trace	SARA312, TSCA
0000103-95-7	Benzenepropanal, .alpha.-methyl-4-(1-methylethyl)-	Trace	SARA312, TSCA
0026027-38-3	ETHOXYLATED NONYLPHENOL W/ POLYALKYLENE GLYCOL	Trace	SARA313, SARA312, VOC, TSCA
0000109-86-4	2-METHOXYETHANOL	Trace	SARA313, CERCLA, HAPS, SARA312, VOC, TSCA, ACGIH, California Proposition 65 - Developmental - Toxicity Male, OSHA


Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	/ 1
FLAMMABILITY	2
Physical Hazard	0
Personal Protection	B

NFPA



(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.